ACTUATECH S.p.A.
Via San Lorenzo 70
Villa Carcina (BS) Italy
Tel +390308908142

GD (double acting) pneumatic actuator, low temperature (-50°C / +60°C)

Macro DA & SR Pneumatic Actuators

Category Special version on request produced by ACTUATECH

On request

benefits



ACTUATECH S.p.A.
Via San Lorenzo 70
Villa Carcina (BS) Italy
Tel +390308908142

1.Energized and self-lubricated strips
Less friction between piston and cylinder
It prevents the bonding of the seal to the cylinder even after long periods of inactivity

2.Slots, bushes and pins made by steel with hardness higher than 50 HRC
Higher resistance to the forces inside the actuator

3.Rolling friction between piston and slot
Less friction

4.Scotch yoke with rolling friction (transforming rotary motion into linear motion using piston and shaft without teeths/gears)
Reduced friction between piston and shaft with consequently less wear on the relevant parts
Empowered Breakaway Torque (BTO & BTC)
Smaller volume/size than rack and pinion actuators (with the same torque) therefore less space required for installation
Less weight than the rack and pinion (-30% kg / Nm), with consequent savings on the construction sizing of the plant/equipment
Lower air consumption compared to the rack and pinion actuators (-40% air cm3/Nm for Double Acting and -20% air cm3/Nm for Spring Return) therefore less load on the compressor or the possibility of using a smaller compressor's size.

5.Rolled cylinder
Less wear of the energized ties thanks to the low roughness of the surface

6.Stainless steel shaft
Higher corrosion resistance

From sizes bigger than GD15, NAMUR interface for solenoid valve is already integrated
No need for extra plate.

100% in- house manufacturing process technology
Maximum control and accuracy in all the stages of the manufacturing process

ATEX Certificate
Installation is allowed in a potential explosive environment

Up to SIL 3 Certified
Guarantee of the high level of functional safety.